



QR Code for Mobile

ROY STAGE LIGHT CO LIMITED

Add : No.4 Dayang Road, Tanbu town, Huadu District, GuangZhou City, China

Email : sales@roylite.com

WhatsApp / Tel : +86 137 1912 2593

Web: www.roylite.com

 $\star \star \star \star \star$

PROFESSIONAL SHOW LIGHTING

ABOUT US

ROY STAGE LIGHT CO LIMITED is a stage lighting equipments manufacturer and distributor, we have been producing stage lights in Guangzhou City, China since 2012, using a combination of quality raw materials, new technology, and a skilled and dedicated work force.

Being a reliable manufacturer in Stage Lighting equipments, we are confident to provide you with everything that's perfect for you every time.

When your customers want something that's good quality but on a tight budget, our products is ideal. Everything is manufactured to our own high standards but comes with a price for you to compete in your market.

We help for special orders. Every now and then you might need something that isn't already within our product lines,but well always have the ideal solution to get you what you want.

WE GROW BY HELPING OUR CUSTOMERS GROW. We're always on your side - and well do whatever we can to help your business succeed. From our great prices and quality products to great services, we'll give you everything you need to help close the deal.

D

实用新型专利证书

Patent

Sourcing service for relevant products is also available, we are always here for you.

Welcome to visit our factory in Guangzhou city, guangdong province, China !



PROFESSIONAL SHOW LIGHTING



TABLE OF CONTENTS

Beam Spot Moving Head

LED Wash Moving Head

IP20 Static Lights

IP65 Outdoor Lights

LED Studio Lights

18R Beam Spot Wash



Model : R-BSW380 Lamp : Osram HRI 371w Brand : ROYLITE Beam angle : 1.5° - 40°

Osram HRI R18 371w bulb,Beam angle 1.5°- 40° zoom,16 circular prisms and 6 linear prisms.1 color wheel,1 rotate gobo wheel,1 fixed gobo wheel,24 DMX channels,Beam 10m - 190000 lux

Lamp type: Osram HRI 371w bulb, lifespan 2200 hours Color temp: 8000K Lens : high precision optical lens Beam angle: 1.5° - 40° linear zooming 14 color filters + white, color rainbow can be created 1 rotating gobo wheel with 7 gobos + white, with the features of self-rotating, water running and shaking effects.gobo wheel can be positioned

Sharp Beam 500



Model : R-MB500Brand : ROYLITELamp : Osram HRI 420wBeam angle : 0 - 2°Suitable for outdoor big event, High output Osram 420W Bulb, beam angle 0 -2.8°, 16 colors, 17 metal gobos. with 3 types of prisms. 10m - 700000 lux beamlens diameter 180mm

Lamp type: Osram HRI 420w Life time 2000 hours

Reflector: Lamp and reflector together in one unit Color temp : 8000K

Beam angle: 0 - 2°

Lens: Glass optical 3 lens group 1 Fixed color wheel with 14 color filters + white two-way rotating and rainbow effect

Sharp Beam 400



Model : R-MB400Brand : ROYLITELamp: Osram HRI 311wBeam angle : 0 - 2°Suitable for big event, High output Osram 311W Bulb, beam angle 0 - 2.8°, 13 colors,17 metal gobos. with 3 types of prisms. 10m - 450000 lux,beam diameter 160mmLamp type: Osram HRI 311w bulblifespan 2500 hoursColor temp 8000KReflector: Lamp and reflector together in one unitLens : high precision optical lens,160mm diameterBeam angle: 0 - 2°13 color filters + white, color rainbow can be created17 fixed metal gobos+white

Sharp Beam 300



Model : R-MB300 Lamp : Osram HRI 251w Brand : ROYLITE

Beam angle : 0 - 2°

Osram HRI 251w bulb, beam angle 0 - 2°, equipped double prisms, 1pcs 16-facet circular prism,1pcs 6-facet linear prism. 14 colors and 17 gobos. 10m - 400000 lux,beam lens diameter 152mm

Lamp type: Osram HRI 251w bulb life time 4000 hours

Color temp : 8000K

Beam angle:0 - 2°

Lens: Glass optical 3 lens group,152mm diameter

1 Fixed color wheel with 14 color filters + white

two-way rotating and rainbow effect

1 Gobo wheel with 17 gobos+white

LED Beam 200w



Model: R-LMB200 LED : white 200w Brand : ROYLITE Beam angle :0- 2°

This is a LED based Moving head beam light, 14 colors and 17 gobos, with 3 types of prisms, LED lifetime is 30000 hours.10m - 180000 lux,beam lens diameter 160mm Lamp type: High quality pro-moduled white LED 200w lifespan 30000h Color temp : 6500K

Beam angle: 0-2°,

Lens: Glass optical 3 lens group

1 Fixed color wheel with 14 color filters + white two-way rotating and rainbow effect

1 Gobo wheel with 17 gobos+white

1 rotating 8-facet prism with moving effect, 1 frost effect, dimming and strobe

LED Beam Spot Wash 250w



Model : R-BSW250Brand : ROYLITELED : white 250wBeam angle : 4 - 35°This is a 250w LED Moving head, Beam spot wash 3 in 1,Beam angle : 4 - 35°,9color filters, 10 fixed gobos and 7 rotate gobos,3 facets circular prism.

Lamp Type: Super bright 250w white LED Lens: coated with anti-reflection film lens Beam Angle: 4 - 35° 9 color filters + white light, color rainbow can be created, two colors move with gradient effect (linear movement), color wheel bidirectional rotation, color at random mode 1 rotating gobo wheel with 4 glass + 3 metal gobos

LED Beam spot wash 400w CMY



Model : R-BSW400	Bra
LED Module : white 400w	Zo
This is LED based beam snot wash 3 in 1 mov	vina hes

Brand : ROYLITE Zoom , CMY , CTO

This is LED based beam spot wash 3 in 1 moving head, with a 400w white LED engin, Beam angle zooming 4° - 35°, with CMY + CTO color mix system.

Source: 400W White LED(6000K) , 20000 Im Zoom: 4°- 35° linear zoom Prism: 3-facet circular rotating prism Frost: 1 frost filter 7 Clor filters linear change CMY+CTO variable color mixing for infinite color possibilities 1 static Gobo Wheel with 7 metal gobos plus open 1 rotating Gobo Wheel with 6 interchangeable glass gobos

LED Beam spot wash 500w CMY

Model : R-BSW500Brand : ROYLITELED Module : white 500wZoom , CMY , CTOThis is LED based beam spot wash 3 in 1 moving head,with a 500w white LEDengin,Beam angle zooming 3.5° - 50°,with CMY + CTO color mix system.

Source: 500W White LED(6000K) , 21000 Im Zoom: 3.5°- 50° linear zoom Prism: 3-facet circular rotating prism Frost: 1 frost filter 7 Clor filters linear change CMY+CTO variable color mixing for infinite color possibilities 1 static Gobo Wheel with 7 metal gobos plus open 1 rotating Gobo Wheel with 6 interchangeable glass gobos

LED Framing Moving Head 600w



Model: R-LPM600 LED : white 600w Brand : ROYLITE Framing,CMY,CTO,Zoom

this is a High brightness framing light, with Module LED 600w engine,beam angle zooming 6° - 48°,CMY + CTO Colormix system . 4 individual framing shutters/blades.

Light Source: 600W White LED, 27000 Im Zoom: 6° - 48° linear motorized Prism: 3-facet circular prism, and 6-linear prism Dimmer: 0-100% variable linear dimming curves CRI Filter: CRI>90 Shutters: 4 independent framing shutters 7 Dichoric Colors plus open, Index / Bi-directional rotating rainbow effect CMY + CTO Colormix system CT 2700K - 6500K Without Gobo wheel

LED Spin Eye 19 x 40w IP



Model: R-R-SE1940IP LED : 19x40w RGBW Brand : ROYLITE Beam angle : 7 - 45°

19 x 40w RGBW 4 in 1,angle 7° - 45°, gives color beam and big angle wash effect, lens rotate to make kaleidoscope effect , each LED control separately.outdoor waterproof IP65 !

AC100-240V Input Power: 800W 19pcs 40w RGBW 4 in 1 LEDs Average Life Span>30,000 h Beam Angle: 7° - 45° DMX Control Channel: 21/23/35/78/97/99 channels

LED Beam Wash 12 x 40w



Model : R-LBW1240Brand : ROYLITELED : 12 x 40w RGBWBeam angle : 5 - 50°this is a LED wash moving head with zoom,with 12pcs 40w RGBW 4 in 1LEDs,beam angle zooming 5°-50°, each LED control separately.

12pcs 40w RGBW 4 in 1 LEDs Average Life Span > 50,000 h Beam Angle: 5° - 50° Lens: High-quality PMMA optical lens All-optical domain dimming, 65536 grade dimming accuracy High light output, low glare Fast strobe: 1-25Hz

LED Beam Wash 7 x 40w



Model: R-LBW740 -LED : 7 x 40w RGBW Brand : ROYLITE Beam angle : 5 - 50°

this is a LED wash moving head with zoom,with original 7pcs 40w RGBW 4 in 1 LEDs.beam angle zooming 5°-50°,each LED control separately.

7pcs 40w RGBW 4 in 1 LEDs Average Life Span > 50,000 h Beam Angle: 5° - 50° Lens: High-quality PMMA optical lens All-optical domain dimming, 65536 grade dimming accuracy High light output, low glare Control Channel: 8 /16 / 32 / 40 control channel models

LED Beam Wash 19 x 15w



Model : R-LBW19Brand : ROYLITELED : 19x15w RGBWBeam angle : 8 - 54°high quality RGBW 4 in 1 LEDs, each LED total power 15w,1 9pcs such LEDs separated as 3 circular pixels.Beam angle linear zooming from 8°-54° .give narrow beam wash and wide angle wash effect19pcs 15w RGBW 4 in 1 LEDsAverage life span N 50,000 hBeam Angle: 8° - 54° linear zoomingLens: High-quality optical lensAll-optical domain dimmingHigh light output, low glare

Fast Strobe: 1-25HZ Control Channel: 20CH / 37CH control channel model

LED Beam Wash 37 x 15w



Model : R-LBW37 LED : 37x15w RGBW Brand : ROYLITE Beam angle : 8 - 45°

high quality RGBW 4 in 1 LED 15w, 37pcs such LEDs separated as 10 pixels.Beam angle linear zooming 8°- 45°, give narrow beam and wide angle wash effect, Low noice fan cooling !

37pcs 15w RGBW 4 in 1 LEDs Average life span≥50,00h Beam Angle: 8° - 45° linear zooming Lens: High-quality optical lens All-optical domain dimming Pan 540°, Tilt 270° Control Channel: 24CH / 32CH control channel model

LED Moving Matrix 25 x 15w



Model : R-LMM25 LED : 25x15w RGBW Brand : ROYLITE Beam angle : 6°

this is a 5 x 5 LED moving matrix light, with 25pcs high power 15w RGBW 4 in 1 Cree LEDs, beam angle 6°, each LEDs control separately, pan tilt unlimited moving.

High quality LED 15w RGBW *4* in 1 25pcs Average life span > 50,000h LED Lens: 6° 0-100% brightness adjustment Fast speed strobe 1-18/sec. 8 built-in programs Control Channel: 19CH / 29CH / 117CH control channel model

LED Spin Eye 19 x 15w



Model : R-SE19

Brand : ROYLITE

LED : 19x15w RGBW

Beam angle : 4 - 60°

19pcs high quality RGBW 4 in 1 LED chip,each of them super powerful 15w,beam angle linear zooming 4° - 60°, and the lens rotationable to make more vivid effects, each LED control separately.

19pcs 15w RGBW *4* in 1 LEDs Average Life Span>50,000 h Beam Angle: 4° - 60° Lens: High-quality PMMA optical lens, Lens rotation functional. All-optical domain dimming, 65536 grade dimming accuracy High light output, low glare Fast strobe: 1-25Hz Color macro and gradual color change effects Control Channel: 21/23/35/78/97/99 control channels

LED Spin Eye 7 x 15w



Model: R-SE7 LED : 7x15w RGBW Brand : ROYLITE Beam angle : 4 - 60°

this is a mini eye moving head, with 7pcs 15w RGBW 4 in 1 LEDs, each LED control separately, beam angle zooming 4° -60°, and lens rotation.

7pcs 15w RGBW 4 in 1 LEDs Average Life Span > 50,000 h Beam Angle: 4° - 60° Lens: High-quality PMMA optical lens, Lens rotation functional. All-optical domain dimming, 65536 grade dimming accuracy High light output, low glare Fast strobe: 1 -25Hz Color macro and gradual color change effects Pan 540°, Tilt 240° Control Channel: 8/ 16/32 /40 control channel models

LED Spin Eye 19 x 40w



Model : R-SE1940

Brand : ROYLITE

LED: 19x40w RGBW

Beam angle : 4 - 60°

19pcs high quality RGBW 4 in 1 LED chip,each of them super powerful 40w,beam angle linear zooming 4° - 60°, and the lens rotationable to make more vivid effects, each LED control separately.

19pcs 40w RGBW *4* in 1 LEDs Average Life Span>30,000 h Beam Angle: 4° - 60° Lens: High-quality PMMA optical lens, Lens rotation functional. All-optical domain dimming, 65536 grade dimming accuracy High light output, low glare Fast strobe: 1-25Hz Color macro and gradual color change effects Control Channel: 21/23/35/78/97/99 control channels

LED Spin Eye 7 x 40w



Model: R-SE740 LED : 7x40w RGBW Brand : ROYLITE Beam angle : 4 - 60°

this is a mini eye moving head, with 7pcs 40w RGBW 4 in 1 LEDs, each LED control separately, beam angle zooming 4° -60°, and lens rotation.

7pcs 40w RGBW 4 in 1 LEDs Average Life Span > 30,000 h Beam Angle: 4° - 60° Lens: High-quality PMMA optical lens, Lens rotation functional. All-optical domain dimming, 65536 grade dimming accuracy High light output, low glare Fast strobe: 1 -25Hz Color macro and gradual color change effects Pan 540°, Tilt 240° Control Channel: 8/ 16/32 /40 control channel models

LED Moving Bar 5 x 60w



Mode : R-LMB560Brand : ROYLITELED : 5x60w RGBWBeam angle : 4-45°Product description: high quality RGBW 4 in 1 LED 60w x 5pcs, and strobe LED42x 3W White LED + 84x 0.3W RGB 3in1 .Beam angle linear zooming 4°- 45°,pantilt 360 degree infinite rotating, Low noice fan coolingFront: 5 x 60W RGBW 4in1 LEDBack :42x 3W White LED + 84x 0.3W RGB 3in1 LEDLEDLens: 4 - 45°RGBW color mixing0-100% brightness adjustmentFast speed strobe 1-18/sec.pan tilt 360 degree infinite rotatingControl Channel: 29 / 105 control channel model

Lifting LED Ball



Mode : R-MLB Lifting wire : 3m / 6m

Brand : ROYLITE LED ball : 25cm / 35cm

Product description: No fan noise, very quiet engine with a kinetic LED color ball, lifting speed 0.6m / s, lifting height 3 meters or 6 meters optional.LED color ball diameters 25cm, or 35cm optional. Light Source: 54pcs tricolor RGB SMD LEDs TOTAL 27W RGB color mixing, LED ball diameter 25CM, 35CM optional 3-pin and 5-pin XLR connectors Powercon In/Out for daisy-chain Lifting wire 3 meters / 6 meters Lifting speed 0.6 m/s Load with cable Maximum 1.8 kgs Machanical Safty control device

Mini LED Beam 36x3w



Brand : ROYLITE Mode : R-LMB108 LED: 36x3w RGBW Beam angle : 6° Product description: This is a mini LED beam moving head light, with 36pcs 3w RGBW LEDs, beam angle 6°, pan tilt speed super fast. Low noice fan cooling !

36pcs 3w RGBW Average life span≥30,000h LED Lens: 6° **RGBW** color mixing 0-100% brightness adjustment Fast speed strobe 1-18/sec. 8 built-in programs Control Channel: 13 control channel model

LED Rotate Bar Zoom 12x40w



Model: R-LBZ1240 LED : 12 x 40w RGBW Brand : ROYLITE Beam angle : 5°- 45°

Tilt moving 260°, beam angle 5°- 45°, with 12pcs 40w RGBW 4 in 1 LEDs, each LED pixel control, special designed optics make it very bright beam&wash, Low noice fan cooling ! 12pcs 40w LEDs, RGBW 4 in 1 Beam angle 5° - 45° Life Span: ≥ 50,000 h Housing: Aluminum stretching material Tilt motorized moving 0 - 260° Powercon In/Out for daisy-chain Protocol: DMX512 Channel Mode: 56ch Control Mode: Pixel control

LED Rotate Bar Zoom 6x40w



Model : R-LBZ640Brand : ROYLITELED : 6 x 40w RGBWBeam angle : 5°- 45°Tilt moving 260°, beam angle 5°- 45°, with 6pcs 40w RGBW 4 in 1 LEDs, each LED pixelcontrol,special designed optics make it very bright beam&wash,Low noice fan cooling !

6pcs 40w LEDs, RGBW 4 in 1 Beam angle 5° - 45° Life Span: ≥ 50,000 h Tilt motorized moving 0 - 260° 3-pin and 5-pin XLR connectors in / out Powercon In/Out for daisy-chain Protocol: DMX512 Channel Mode: 30ch Control Mode: Pixel control

LED Strobe 3000



LED Strobe / Wash 1000



Model : R-LS3000Brand : ROYLITELED : RGB +W10w white LED 240pcsThis is a High power LED strobe light, with 240pcs 10w white LEDs for strobe, background64pcs 0.6w RGB LEDs.

strobe : 10w white LED 240pcs, background: 0.6w RGB LED 64pcs Life Span:≥50,000 h Power Supply: 100-240V 50/60 Hz Input Power: 3000W DMX Channel Mode: 4CH / 14CH Control Panel: LED display+ button Strobe Speed: 0.5-25Hz/50 Hz Ac 0.6-30Hz/60 Hz Ac Model : R-LSL1000 LED : RGB / W / RGBW Brand : ROYLITE 960pcs SMD 0.5w

SMD5050 LED 960pcs 0.5w,beam angle 60°,3 versions: RGB 3 in 1 version with 8 pixels control,,White LED version with 4 pixels control,,RGBW 4 in 1 version,with no pixel control.Low noice fan cooling !

Light Source

- A: RGB 3 in 1 0.5W LED, 960pcs, 8 pixels control (default)
- B: White color 0.5W LED, 960pcs, 4 pixels control
- C: RGBW 4 IN 1 0.5W LED, 960pcs, no pixel control Protocol: DMX512 Channel Mode: 8CH / 16CH / 52CH Control Panel: LED display+ button

Strobe Speed: 0.5-25Hz/50 Hz Ac 0.6-30Hz/60 Hz Ac

LED Studio Par Color Wash





Model : R-LSS4824Brand : ROYLITELED : RGB +W480pcs SMD 0.5w RGBSMD5050 LED 480pcs 0.3w RGB, and 240pcs 0.5w white LEDs,72 pixels control .Lownoice fan cooling !

LED 480pcs 0.3w RGB, and 240pcs 0.5w white LEDs, 72 pixels control Life Span:≥50,000 h Protocol: DMX512 Channel Mode: 16CH / 168CH Control Panel: LED display+ button Strobe Speed: 0.5-25Hz/50 Hz Ac 0.6-30Hz/60 Hz Ac Model: R-LSP LED : 18x8w RGBW Brand : ROYLITE Beam angle : 25°

this is a very quiet working LED par light, without fan cooling it cool by its own heavy aluminum body, Dimming is super smooth 16bits, flicker free for video.

A: 18 x 8w RGBW 4 in 1 LEDs, (Default) B: 18 x 12w RGBWA+UV 6 in 1 LEDs Average Life Span: >30,000h Lens: 25° optional 45° smooth linear dimmer High light output, low glare Fast speed strobe 1 ~25Hz Color macro and gradual color change effects Control channel: 8 control channel modes

LED Par Zoom 19 x 15w



Model : R-LPZ19Brand : ROYLITELED : RGBWBeam angle : 10° - 60°This is a LED par light with zoom, 19pcs high power LEDs, RGBW 4 in 1 ,beam angle
zooming 10° - 60°,Low noice fan cooling !

Lamp : 19 x 15w RGBW 4 in 1 LED Average Life Span: > 50,000h Lens: 10° - 60° linear zooming RGBW 4 in 1 smooth linear dimmer High light output, low glare Fast speed strobe 1~25Hz Color macro and gradual color change effects Control channel: 18 control channels

LED Par Zoom 18 x 8w



Model : R-LPZ18 LED :18 x 8w RGBW Brand : ROYLITE beam angle : 10° - 60°

this is a LED color wash light with zoom,beam angle zooming 12° - 58°, with 18pcs 10w RGBW 4 in 1 LEDs.16 bits smooth dimming.Low noice fan cooling.

Lamp : 18 x 10w RGBW 4 in 1 LEDs Average Life Span: > 30,000h Lens: 12° - 58° linear zooming smooth linear dimmer High light output, low glare Fast speed strobe 1 ~25Hz Color macro and gradual color change effects Control channel: 9 control channel modes

LED Par Light 18pcs



Model: R-LP18Brand : ROYLITELED : 18 x 8w RGBWBeam angle : 25°This is a LED color wash light with high power 8w or more, Multi-chips LED. beamangle 25° or 40°,Low noice fan cooling

A: 18 x 8w RGBW 4 in 1 LEDs, (default) B: 18 x 12w RGBWA+UV 6 in 1 LEDs Average Life Span: > 30,000h Lens: 25° optional 40° smooth linear dimmer High light output, low glare Fast speed strobe 1 \sim 25Hz Color macro and gradual color change effects Control channel: 8 control channel modes

LED Par Light 24pcs



Model: R-LP24 LED : 24 x 8w RGBW Brand : ROYLITE Beam angle : 25°

This is a LED color wash light with high power 8w or more, Multi-chips LED. beam angle 25° or 40°,Low noice fan cooling

A: 24 x 8w RGBW 4 in 1 LEDs, (default) B: 24 x 12w RGBWA+UV 6 in 1 LEDs Average Life Span: > 30,000h Lens: 25° optional 40° smooth linear dimmer High light output, low glare Fast speed strobe 1 \sim 25Hz Color macro and gradual color change effects Control channel: 8 control channel modes

LED Par 36 x 8w



Model : R-LP360Brand : ROYLITELED : 36 x 8wBeam angle : 25° / 40°this is a high power LED color wash with 36pcs high quality 8w RGBW LEDs,16bitssmooth dimmer,and low noice fan cooling, lens 25°, 40° for options.Low noice fancooling !

36 x 8w RGBW 4 IN 1 LEDs Average Life Span: > 50,000h Lens: 25° optional 40° smooth linear dimmer High light output, low glare Fast speed strobe 1~25Hz Color macro and gradual color change effects Control channel: 8 control channel modes

Mini LED Par 7 x 8w



Model : R-LP7x8Brand : ROYLITELED : 7 x 8w RGBWBeam angle : 25°,40°this is a Mini LED color wash with 7pcs 8w LEDs,RGBW 4 in 1, lens 25°, 40° for
options.

7 x 8w RGBW 4 in 1 LEDs Average Life Span: > 50,000h Lens: 25° optional 40° smooth linear dimmer High light output, low glare Fast speed strobe 1~25Hz Color macro and gradual color change effects Control channel: 8 control channel modes

COB Par Blinder 200w



Model: R-COB200Brand : ROYLITELED : COB 200wBeam angle : 60°this is a warm white LED par, with one COB 3000K LED, power is 200w,beam angle 60°,warm white and cool white 2 in 1 LED for option.Low noice fan cooling !

LIGHT SOURCE

A - 200W COB LED, warm white , color temp 3000K B - 200W COB LED, warm white and cool white 2 in 1 Life Span: 30000 h Lens: 60° Housing: Aluminum material Structure: available for vertical/horizontal splicing 3-pin or 5-pin XLR connectors AC: 100-240V 50/60 Hz Input Power: 210W

COB Blinder With Zoom



Model: R-LBZ LED : 200w or 300w Brand : ROYLITE Beam angle : 15 - 60°

This is a blinder light, 200w / 300w LED source warm white or cool white ,beam angle zooming 15° - 60°.Low noice fan cooling !

Lamp : 200w or 300w white LED. warm white or cool white Average Life Span: > 30,000h

Lens: 15° - 60° linear zooming High light output, low glare Fast speed strobe 1 ~25Hz Color macro and gradual color change effects Control channel: 8 control channel modes Protocol: Standard DMX512 Menu display: LED display

Warm COB Blinder 2 x 100w



Model : R-COB2EBrand : ROYLITELED : 2 x 100wBeam angle : 60°this is a warm white 2 eyes LED blinder, with 2pcs COB 3200K LED, each LED100w,beam angle 60°, optional version cool white LEDs.Low noice fan cooling !

A - $2 \times 100W$ COB LED, warm white , color temp 3200K B - $2 \times 100W$ COB LED, cool white ,color temp 6400K Life Span: $\geq 30,000$ h Lens: 60° Housing: Aluminum material Structure: available for vertical/horizontal splicing AC: 100-240V 50/60 Hz Input Power: 210WProtocol: DMX512 Channel Mode: 5CH,3CH

Warm COB Blinder 4 x 100w



Model : R-WB4 LED : 4 x 100w Brand : ROYLITE Beam angle : 60°

this is a high power blinder light with 4pcs warm white LEDs,each 100w total 400w, color temp 3200K.each LED control separately.Low noice fan cooling !

4pcs x 100W COB LEDs,color temp 3200K,warm white optional version cool white 6400K LEDs. Life Span: ≥ 30,000 h Lens: 60° 3-pin or 5-pin XLR connectors Powercon In/Out for daisy-chain Channel Mode: 1CH,3CH,4CH,9CH Control Mode: Pixel control

Warm COB Blinder 4 x 50w



Model : R-COB450Brand : ROYLITELED : 4 x 50wBeam angle : 60°this is a warm white LED blinder, with 4pcs COB 3200K LED, each LED 50w,beamangle 60°, optional version cool white LEDs.Low noice fan cooling !

A: COB LED 4 x 50w warm white 3200K (Default) B: COB LED 4 x 50w cool white 5600K C: COB LED 2 x 50w warm white 3200K ,2 x 50w cool white 5600K Life Span: \geq 30,000 h Lens: 60° Housing: Aluminum material Structure: available for vertical/horizontal splicing AC: 100-240V 50/60 Hz Input Power: 210W Protocol: DMX512 Channel Mode: 8CH,6CH LED Blinder 5



Model : R-LB5	Brand : ROYLITE
LED : 5pcs 30w RGB	Beam angle : 58°
This is a pixel blinder bar light,	with 5pcs 30w RGB 3 in 1 LEDs, beam angle
58 $^\circ$,each LED control separately	

5x30w RGB 3 in 1 Life Span: > 30,000 h Lens: 58° Housing: Aluminum stretching material 3-pin or 5-pin XLR connectors Powercon In out AC: 100-240V 50/60 Hz Input Power: 160W

LED Blinder 5x5



LED Strip Light 18 x 8w



Model : R-LB5x5	Brand : ROYLITE
LED : 25x10w RGBW	Beam angle : 58°
this is a pixel mapping LED blinde	r, with 25pcs high power 10w RGBW 4 in 1 LEDs,
each LED control separately,beam ar	ngle 58°
25pcs x 10W RGBW 4 in 1 LEDs	
Life Span: 50,000 h	
Lens: 58°	
Housing: Aluminum stretching materia	al
Structure: available for vertical/horizo	ontal splicing

3-pin or 5-pin XLR connectors

Powercon In/Out for daisy-chain

Model : R-LPW18 LED : 18x8w RGBW Brand : ROYLITE Beam angle : 25°

this is a pixel mapping LED strip, with 18pcs high power 10w RGBW 4 in 1 LEDs, each LED control separately.beam angle 15 °, 25 °, 45 ° for options.DMX channels models 8CH,14CH,26CH,74CH.Low noice fan cooling !

18pcs x 8W RGBW 4 in 1 LEDs
Life Span: 50,000 h
Lens: 25°
Housing: Aluminum stretching material
Structure: available for vertical/horizontal splicing
3-pin or 5-pin XLR connectors
Powercon In/Out

LED battery Uplight



Model : R-LBU6Brand : ROYLITELED : 6 x 12w RGBWAUVApp.Wireless DMX,remotethis is a LED battery Uplight,6pcs 12w RGBWA+UV 6 in 1 LEDs,beam angle 25° ,mobil APP, wireless DMX,remote,3 control ways, up to 8 hours working time.

6x 12w RGBWA+UV 6 in 1 LEDs Average Life Span: >30,000h Lens: 25° optional 45° RGBWA+UV 6 in 1 smooth linear dimmer High light output, low glare Fast speed strobe 1 ~25Hz Color macro and gradual color change effects

Battery LED Uplight 3pcs



Model : R-LBU3Brand : ROYLITELED : 3 x 12w RGBWAUVApp,Wireless DMX,remotethis is a LED battery Uplight,3pcs 12w RGBWA+UV 6 in 1 LEDs,beam angle25°,mobile APP, wireless DMX,remote,3 control ways, up to 8 hours working time.3 x 12w RGBWA+UV 6 in 1 LEDs, Average Life Span: >30,000hLens: 25° optional 40°Control channel: 6 / 10 control channel modesWIFI control,mobile App,IOS or AndriodBuilt in 2.4G wireless DMX receiverBattery time displayBattery capacity 10000mahBattery last time : full on 3 hours, colors running 6 hours, single color 8 hourswithout Fan cooling,quiet working

Mini LED Profile Zoom 60w

Model : R-MPZ60Brand : ROYLITELED : warm / cool white 60wBeam angle : 15°-30°mini compact body,Color temp 3200k or 6500k optional , super silent fan with copperliquid cooling,clear spot cut edge,high bright even spot,flicker free for Camera

single 60w LED, warm white 3200k, or cool white 6500k CRI: Ra≥90

Life Span: \geq 50,000 h Beam angle zoom: 15° - 30° Housing: Die-casting alumimnum AC: 100-240V 50/60 Hz Input Power: 60W Protocol: DMX512,super smooth 16 bit dimming Channel Mode: 1CH ,3CH

LED Profile Light 600w CTO



Model : R-P600 LED : warm+cool white 600w Brand : ROYLITE Beam angle : 19°/26°/36°/50°

Color temp 3000k - 6000k linearly controlled by one DMX channel, super silent fan with copper liquid cooling, clear spot cut edge, high bright even spot, flicker free for Camera

single 600w LED, warm white and cool white 2 in 1 Life Span: > 30,000 h Lens: 19°/26°/36°/50° Housing: Aluminum stretching material 3-pin or 5-pin XLR connectors, Powercon In out AC: 100-240V 50/60 Hz Input Power: 650W

LED Profile 300w Light



Model : R-P300Brand : ROYLITELED : warm / cool white 300wBeam angle : 19°/26°/36°/50°Color temp 3000k or 6000k optional , super silent fan with copper liquid cooling,clearspot cut edge,high bright even spot,flicker free for Camera,

single 300w LED, warm white 3200K or cool white 5600K for options Life Span: 30,000 h Lens: 19°/26°/36°/50° Housing: Aluminum stretching material 3-pin or 5-pin XLR connectors Powercon In/Out for daisy-chain AC: 100-240V 50/60 Hz Input Power: 350W

LED Profile 200w Light



Model : R-P200 LED : warm / cool white 200w Brand : ROYLITE Beam angle : 19°/26°/36°/50°

Color temp 3000k or 6000k optional , super silent fan with copper liquid cooling,clear spot cut edge,high bright even spot,flicker free for Camera

single 200w LED, warm white 3200K or cool white 5600K for options Life Span: 30,000 h Lens: 19°/26°/36°/50° Housing: Aluminum stretching material 3-pin or 5-pin XLR connectors Powercon In/Out for daisy-chain AC: 100-240V 50/60 Hz Input Power: 250W

LED Profile Zoom 200w



 -Model : R-PZ200
 Brand : ROYLITE

 -LED : warm / cool white 200w
 zoom : 19° -36°

Color temp 3200k or 6500k optional, super silent fan with copper liquid cooling, clear spot cut edge, high bright even spot, flicker free for Camera

LIGHT SOURCE

single 200w LED, warm white 3200k, or cool white 6500k CRI: Ra≥90 Life Span: ≥ 50,000 h Beam angle zoom: 19° - 36° **FEATURES** Housing: Die-casting alumimnum material 3-pin or 5-pin XLR connectors **ELECTRICAL** AC: 100-240V 50/60 Hz Input Power: 230W

LED Fresnel 200w



Model : R-LF200

Brand : ROYLITE

LED : 200w

Beam angle : 19° or 26°

this is a LED fresnel light, with high quality single 200w LED, warm white or cool white for options. beam angle 19° or 26° , super smooth 16-bit

dimming .CRI>90. LIGHT SOURCE single 200w LED, warm white 3200K or cool white 6500K for options Life Span: ≥ 30,000 h OPTICAL SYSTEM Beam angle: 19° or 26° FEATURES Housing: Aluminum stretching material 3-pin or 5-pin XLR connectors Powercon In / out ELECTRICAL AC: 100-240V 50/60 Hz Input Power: 200W

LED Fresnel Zoom



-Model : R-LFZ -LED : 200w / 300w Brand : ROYLITE

zoom : 15° -50°

this is a LED fresnel light, with high quality single 200w / 300w LED, warm white or cool white for options, beam angle motorized zooming 15° - 50", super smooth 16-bit dimming .CRI>95.

LIGHT SOURCE

A : single 200w LED, warm white 3000K or cool white 5600K for options B : single 300w LED, warm white 3000K or cool white 5600K for options Life Span: > 30,000 h

Beam angle: 15° - 50° linear zooming Housing: Aluminum stretching material 3-pin or 5-pin XLR connectors

LED Video Panel Light



Model : R-LVPBrand : ROYLITELED : 150wWarm white or cool whitethis is a LED video panel light, with high quality White LED 384pcs, warm white3200k or cool white 6500k for options. super smooth 16-bit dimming .CRI>90.without fan noice,flicker free for camera.version A : SMD LEDs 384pcs warm white 3200Kversion B : SMD LEDs 384pcs cool white 6500KLife Span: \geq 50,000 hBeam angle: 120°Housing: Aluminum stretching material3-pin or 5-pin XLR connectors, Powercon In / outAC: 100-240V 50/60 HzInput Power: 160W

LED Follow Spot 460w



Model : R-LFS460

LED : 420w

Brand : ROYLITE Shooting : 150m

LED 420w,6500K,CRI>90,shooting 150m,clear edge,even spot,5-colors color wheel,5-gobos gobo wheel, beam angle zooming 10° - 65° .

LIGHT SOURCE

LED 420W, 6500K, 3200K optional, CRI>90 Life Span: ≥ 30000 h Beam angle: Linear 10° - 65° **FEATURES** Housing: alumimnum and fireproofing quality plastic Powercon In **ELECTRICAL** AC: 100-240V 50/60 Hz Input Power: 460W

LED Wash / Strobe IP



Model : R-LSW LED : SDM5050 RGB Brand : ROYLITE Beam angle : 68°

SMD5050 RGB LEDs, total LED power 320w, IP65 waterproof, gives super bright RGB color mixing wash and strobe effect.

Light Source: super bright RGB 3 colors in 1 SMD5050, LED total power 320w Life Span:≥50,000 h LED Control: 6 individual segments , separate control Power Supply: 100-240V 50/60 Hz Input Power: 320W Protocol: DMX512 Channel Mode: 3CH / 7CH / 72CH Control Panel: LED display+ button Strobe Speed: 0.5-25Hz/50 Hz Ac 0.6-30Hz/60 Hz Ac

LED Wash / Flood Color 480



Model : R-LWC480Brand : ROYLITELED : 48 x 8w RGBWBeam angle : 25° / 40°this is a LED outdoor washer with 48pcs high power 8w LEDs, each LED has RGBW4 colors, beam angle 25°, IP65 waterproof.

Lamp: 48 x 10w RGBW 4 in 1 LEDs, Average Life Span >50,000h Lens: 25°, optional 40° RGBW 4 in 1 256 grade 0-100% square rate dimmer Fast speed strobe Effect macro and white light gradient effect Control channel: 8 control channel modes

LED Wash / Flood Color 600



Model : R-LWC600 LED : 60 x 10w RGBW Brand : ROYLITE Beam angle : 25° / 45°

this is a LED outdoor washer with 60pcs high power 10w LEDs, each LED has RGBW 4 colors, beam angle 25°,IP65 waterproof. with seetronic IP Powercon True 1 input and output.waterproof fan cooling.

Lamp: 60 x 10w RGBW 4 in 1 LEDs, Average Life Span >50,000h Lens: 25°, optional 45° RGBW 4 in 1 256 grade 0-100% square rate dimmer Fast speed strobe Effect macro and white light gradient effect Control channel: 8 control channel modes

LED Rotate Strobe 1000IP



LED Rotate Washer 44IP



Model : R-LRS1000Brand : ROYLITELED power : 1000wTilt moving : 0 - 185°Waterproof moving strobe light, LED tube with 144pcs 5w white LEDs,4 pixels separately.LED panel with 480pcs 0.5w RGB 3 in 1 LEDs,8 pixels separately.out.support RDM.

LED Type: 5050 0.5W RGB 3in1 LEDs 480pcs LED Segments: 8 (2 x 4) Strobe Tube LEDs LED Type: 3535 5W 6500K LEDs 144pcs LED Segments: 4 Tilt (Degrees): 185° Control Modes: 7CH / 14CH / 42CH Cooling: Temperature controlled, overheating protection Model : R-LRW44Brand : ROYLITELED : 44 x 10w RGBWTilt moving : 0 - 185°Waterproof rotate LED washer, with 44pcs 10w RGBW 4 in 1 LEDs,beam angle25°, motorized tilt moving 0 - 185°, True 1 input and output.support RDM.

Lamp: 44 x 10w RGBW 4 in 1 LEDs, Average Life Span >50,000h Lens: 25°, optional 45° 256 grade 0-100% square rate dimmer Fast speed strobe Effect macro and white light gradient effect CONTROL AND PROGRAMMING Control channel: 7CH,9CH,11CH Protocol: Standard DMX512, RDM Tilt moving 0 - 185° Master/Slave control mode Menu Display: LCD display DMX Signal Connection: 3-pin XLR input/output Aluminum alloy die-casting structure

LED Par Zoom 15 x 15w IP



Model : R-WPZ15Brand : ROYLITELED : 15x15w RGBWBeam angle : 8° - 50°this is a waterproof IP65 LED par light with zoom, beam angle zooming 8° - 50°,with 15pcs 15w RGBW 4 in 1 LEDs,16bits smooth dimming.

Lamp: 15 x 15w RGBW 4 in 1 LEDs Average Life Span >50,000h Lens: 8° - 50° linear zooming 256 grade 0-100% square rate dimmer Fast speed strobe Effect macro and white light gradient effect Control channel: 11 control channels

LED Par Zoom 7 x 40w IP



Model : R-WPZ740Brand : ROYLITELED : 7x40w RGBWBeam angle : 6° - 50°this is a waterproof IP65 LED par light with zoom, beam angle zooming 6° - 50°,with 7pcs 40w RGBW 4 in 1 LEDs,16bits smooth dimming,quiet waterproof fancooling.

Lamp: 7 x 40w RGBW 4 in 1 LEDs Average Life Span >50,000h Lens: 6° - 50° linear zooming 256 grade 0-100% square rate dimmer Fast speed strobe Effect macro and white light gradient effect Control channel: 11 control channels

LED Waterproof Par 18pcs



Model : R-WWP18Brand : ROYLITELED : 18x8w RGBWBeam angle : 25°this is a waterproof LED color wash light, with 18pcs high power multi-ships L

this is a waterproof LED color wash light .with 18pcs high power multi-chips LEDs, super well heat sink to assure long lifespan of the LEDs, beam angle 25°, 45°, for options.

LIGHT SOURCE

A: 18 x 8w RGBW 4 in 1 LEDs, (Default) B: 18 x 12w RGBWA+UV 6 in 1 LEDs, Average Life Span>30,000h Lens: 25°, optional 45° 256 grade 0-100% square rate dimmer Fast speed strobe Effect macro and white light gradient effect Control channel: 8 control channel modes

LED Waterproof Par 24pcs



Model : R-WWP24Brand : ROYLITELED : 24 x 8w RGBWBeam angle : 25° / 40°with 24pcs high power RGBW LEDs,super well heat sink to assure long lifespan of
the LEDs, smooth dimming,beam angle 25°,40° for options.true 1 connectors

24 x 8w RGBW 4 in 1 LEDs Average Life Span>50,000h Lens: 25°, optional 40° 256 grade 0-100% square rate dimmer Fast speed strobe Effect macro and white light gradient effect Control channel: 8 / 4 control channel modes

Mini LED Waterproof Par 7pcs



Model : R-WWP7Brand : ROYLITELED : 7x8w RGBWBeam angle : 25°this is a mini LED waterproof par light, 7pcs LEDs RGBW or RGBWA+UV, super wellheat sink to assure long lifespan of the LEDs, beam angle 25°, 40°, for options.silent

A: 7 x 8w RGBW 4 IN 1 LEDs, (Default) B: 7 x 12w RGBWA+UV 6 IN 1 LEDs Average Life Span >50,000h

operation.

Lens: 25°, 40° 256 grade 0-100% square rate dimmer Fast speed strobe Effect macro and white light gradient effect Control channel: 8 control channel

COB Blinder 200w IP



Model : R-COB200IP LED 200w: RGBW / WW Brand : ROYLITE Angle : 30° / 60°


this is a waterproof blinder light, use single 200w LED, warm white or RGBW for options, beam angle 30 ° or 60° for options, IP65 waterproof.

A - 200W COB LED, warm white , color temp 3000K B - 200W COB LED, RGBW Life Span: 30,000 h Lens: 30° / 60° Housing: Aluminum material Structure: available for vertical/horizontal splicing 3-pin or 5-pin XLR connectors,waterproof Waterproof power cable in and out AC: 100-240V 50/60 Hz Input Power: 210W

LED Strip 18 x 8w Waterproof

LED Strip 24 x 3w Waterproof





Model : R-PWW18Brand : ROYLITELED : 18x8w RGBWBeam angle : 25°this is a Pixel mapping waterproof LED strip light, with 1 8pcs 10w RGBW 4 in 1 LEDs, eachLED control separately, beam angle 25 °, or 45 ° for option. IP65 waterproof. DMX channels8CH, 14CH, 26CH, 74CH

Lamp: 18 x 8w RGBW 4 in 1 LEDs, Average Life Span>30,000h Lens: 25° 256 grade 0-100% square rate dimmer Fast speed strobe Effect macro and white light gradient effect Control channel: 8, 14, 26, 38,74 control channel modes Aluminum alloy die-casting structure Model : R-LWW24Brand : ROYLITELED : 24 x 3w RGBBeam angle : 25°this is a waterproof LED strip light, with 24pcs 3w RGB 3 in 1 LEDs, beam angle25°, or 45° for option. IP65 waterproof. silent operation.

Lamp: 24 x 3w RGB 3 in 1 LEDs, Average Life Span>50,000h

Lens: 25° 45° 256 grade 0-100% square rate dimmer Fast speed strobe Effect macro and white light gradient effect Control channel: 8 control channels Aluminum alloy die-casting structure

Warm COB Blinder 4 x 100w IP



Model : R-WB200IPBrand : ROYLITELED : 2 x 100wBeam angle : 30° / 60°2pcs high power COB LEDs, warm white 3000K, 2 heads can manual adjust angle 0 -24°, IP65 waterproof.

Light Source: 2pcs x 100W COB LEDs, warm white 3000K Life Span: > 30,000 h Housing: Aluminum stretching material each head pan angle manual adjustable 0 - 24° Structure: available for vertical/horizontal splicing 3-pin or 5-pin XLR connectors Powercon In/Out for daisy-chain



Model : R-WB4IP LED : 4 x 100w Brand : ROYLITE Beam angle : 30° / 60°

this is a outdoor high power blinder light with 4pcs warm white LEDs.each 100w total 400w, color temp 3000K. each LED control separately, each head pan angle can be manual adjusted 0 - 24°.IP65 waterproof. Light Source: 4pcs x 100W COB LEDs, color temp 3000K warm white Life Span: 30,000 h Housing: Aluminum stretching material each head pan angle manual adjustable 0 - 24° Structure: available for vertical/horizontal splicing

LED Par Blinder 200w IP



Model : R-LWB200

LED: 4 x 50w

Brand : ROYLITE

Beam angle : 45°

this is a waterproof LED blinder light ,with 4pcs 50w white LEDs,warm white or cool white optional,super well heat sink to assure long lifespan of the LEDs, beam angle 45°.

A: COB LED 4 x 50w warm white 3200K (Default)

B: COB LED 4 x 50w cool white 5600K

C: COB LED 2 x 50w warm white 3200K ,2 x 50w cool white 5600K

Average Life Span>50,000h

Lens: 45°

Control channel: 6 control channel modes

IP65 waterproof

Battery LED Strip 9pcs IP



Model : R-BLS9 LED 9 x 12w RGBWA+UV

Brand : ROYLITE

App,Wireless DMX,remote

this is a LED battery Uplight for outdoor,9pcs 12w RGBWA+UV 6 in 1 LEDs,beam angle 25°,mobile APP, wireless DMX,remote,3 control ways, up to 3 hours working time at full power.

9 x 12w RGBWA+UV 6 in 1 LEDs
Lens: 25° optional 40°
Control channel: 6 / 10 control channel modes
WIFI control,mobile App,IOS or Andriod
Built in 2.4G wireless DMX receiver
Battery time display
Battery capacity 2000mah
Battery last time : full on 3 hours, colors running 5 hours, single color 7 hours

Battery LED Waterproof Par 6pcs



Model : R-BWL6Brand : ROYLITELED 6 x 12w RGBWA+UVApp,Wireless DMX,remotethis is a LED battery Uplight for outdoor,6pcs 12w RGBWA+UV 6 in 1 LEDs,beamangle 25°,mobile APP, wireless DMX,remote,3 control ways, up to 8 hours workingtime.

6 x 12w RGBWA+UV 6 in 1 LEDs Lens: 25° optional 40° Control channel: 6 / 10 control channel modes WIFI control,mobile App,IOS or Andriod 1.77 inch LCD display Built in 2.4G wireless DMX receiver Battery time display Battery capacity 2000mah Battery last time : full on 3 hours, colors running 6 hours, single color 8 hours

Battery LED Waterproof Par 12pcs



Model : R-BWL12Brand : ROYLITELED 12 x 12w RGBWA+UVApp,Wireless DMX,remotethis is a LED battery Uplight for outdoor,12pcs 12w RGBWA+UV 6 in 1LEDs,beam angle 25°,mobile APP, wireless DMX,remote,3 control ways, up to 3hours working time at full power.

12 x 12w RGBWA+UV 6 in 1 LEDs Lens: 25° optional 40° Control channel: 6 / 10 control channel modes WIFI control,mobile App,IOS or Andriod Built in 2.4G wireless DMX receiver Battery time display Battery capacity 2000mah Battery last time : full on 3 hours, colors running 5 hours, single color 7 hours

Sunny 512 DMX Console



Mode : R-DC512Brand : ROYLITEChannels : 512 CHDMX output : 2the sunny 512 DMX console has total 512 DMX channels, with 2 DMX outputs, separatelyoptical isolated.

512 DMX channels with 2 optical isolated output.

32 units with 16 DMX channels each.LCD display.

16 channel faders, 1 chase speed fader, 2 modulation Wheel for 16 bit of Tilt / Pan.

48 chases, total 1600 steps. Each step contains its speed and cross time

48 scenes.

15 environment programs to output the combination,

chases and manual output quickly.

8 chases, 48 scenes can be run simultaneously. At most 32 unit can be Manual operate. Backup or restore with USB Flash drive.

DMX Splitter 8



Model : R-DS8Brand : ROYLITEthis is a electric isolated DMX splitter, with 2 DMX inputs , 3pin or 5pin optional,,DMX signal outputs 8 ways .

Voltage: AC 90V-240V,50HZ/60HZ

Unit size: 482 x 147 x 44mm (19" Rack, 1U)

Unit weight: 3kgs

1-8 DMX signal splitter

DMX signal isolated electrically

XLR 3-pin, 5-pin connectors optional

LED indicators display output data fro each channel independently



Arena Console



Fader wing



Tiger Touch II



Command wing



Quartz



Wing pro



F2 Light



F3 Full Size

Haze Machine 2000w



Spark Cold Fire Machine



Mode : R-HM2000Brand : ROYLITEPower : 2000wControl : DMX, remoteProduct description: This is a strong power haze machine with new technology,
Continuous output,3500Cu ft/min .

Power: 2000W Pre-heating time: 90 seconds Tank capacity: 2.5L Controller: LCD display control and DMX control. Oil shortage protection Overheat protection Can be placed vertically or horizontally DMX channel: 2channels Mode : R-FX600Brand : ROYLITEPower : 600wSpark Height : 1m - 5mProduct description: This is a Spark Cold Fire Machine,spark height 1m to 5m,
remote control and DMX control.

Power: 600W

Voltage: AC110V-250V 50/60Hz

Heating time: 5 min

Sparkular spray height: 1m to 5m

Control mode: Remote Control, DMX512

Output volume can adjust

Power Distributor (Customized)

Accessories




Power Distributor 32A





Power Distributor 63A Power Distributor 63A





Socapex Power Rack



Waterproof CEE Power Distribution



Power Distribution Cabinet



12CH DMX Dimmer Pack

6CH DMX Dimmer Pack



4CH DMX Dimmer Pack







Aluminum Clamps

Aluminum Safty Cables









19Pin Socopex fan out cable

Socopex Cable









DMX cable 3pin / 5pin

Power & DMX 2 in 1 cable

8 ways DMX data looms







3p - 5p XLR adapter

Rain cover

